

支持电池可拆卸
Battery Detachable



百万像素
Million Pixels

5280 蓝牙无线二维影像扫描枪

Cordless 2D Area Imager-Bluetooth



1D / 2D



高速扫描



大视野



“超扫”解码



屏幕扫描



定制开发



运动容差



大容量电池



跌落标准

适用于多种应用场景 / Can be used in multiple application scenarios



超市



商场



仓库

性能优势：

- 多国语言条码信息直传
- 大视角影像感光器
- 高速、全方位的一维、二维码影像读取
- 空旷200m数据传输
- 电池容量2600mAh, Type-C和接触式充电可选
- 可连接底座, iOS、Android手机平板电脑等

Performances:

- Multiple language transmission
- Large viewing angle
- High speed, omnidirectional reading of 1D/2D, Postal barcodes and OCR
- 200 meters working range at open space
- High capacity battery up to 2600mAh; Charged with Type-C and cradle
- Can work with Apple iOS, Android, Window PC etc.

5280 技术规格书 / Technical specification

物理参数 / Physical Characteristics

尺寸Dimensions:	180mmx95mmx70mm
重量Weight:	212g
电压Voltage/电流Current:	5VDC+/-10%@500mA

识读参数 / Performance Characteristics

图像传感器Image(Pixels):	1280 pixels(H) x 1080 pixels(V)
光源Light Source:	illumination: 4000KLED+617nmLED
视场角Field Of View:	38.5°(H)x32.5°(V)
旋转倾斜偏移Roll/Pitch/Yaw:	倾斜/Pitch $\pm 65^\circ$ 旋转/Yaw 360° 偏转/Roll $\pm 60^\circ$
电池容量Battery Volume:	4.2v/2600mAh
充电时间Charging time:	5-6h
续航时间Working time:	Continuously working 16H, 1 scan per second(full capacity)
无线技术Wireless technology:	Bluetooth 5.0
操作距离Operation distance:	200 meters (open space)
打印对比度Print Contrast:	15% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
运动容差Motion Tolerances:	2m/s
识读码制 Decode Capability:	一维条码/1D: UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar, Interleaved 2 of 5, etc
	二维条码/2D: PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, etc.

用户环境 / User Environment

工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
抗震动Shock Specifications:	Designed to withstand 1.5m(5) drops
环境光免疫Ambient Light Immunity:	100,000 Lux.

典型码识读距离 / Decode Ranges

Code 39 (3.13 mil):	35mm-80mm	Code 39 (5.13 mil):	35mm-165mm
PDF(6.88 mil):	20mm-210mm	DM (10 mil):	50mm-230mm
UPC-A (13.3 mil):	25mm-390mm	QR (20 mil):	20mm-410mm

