

Shipping & Sticker Barcode Printer



Key Features

- Faster print speed up to 203mm(8inch)/sec
- 203DPI resolution for high-performance label printing
- Flexible connectivity options: USB/USB Host/ Ethernet/Wi-Fi/Bluetooth
- Multiple emulations preinstalled for easy system integration
- No need ribbon, work with 20~120mm thermal sticker labels.





ELITE SERIES 4" Direct Thermal Barcode Printer

MODEL	GE-2408D
Resolution	203DPI
Print Method	Direct Thermal
Print Speed	8" /second
Print Width	104mm(4.1")
Memory RAM	128 MB SDRAM
Memory ROM	128 MB Flash Memory
Interface	Standard configuration interface :1.USB 2.USB host 3.Ethernet Optional accessories :Serial /BT /WiFi Support mode :Serial +BT/Serial +WiFi/BT+WiFi (Serial port not yet supported)
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix
Emulations	TSPL, ZPL, ZPL II, EPL, DPL
Compact dimension	243mm (D) x 194mm (W) x 183mm(H)
Net Weight	2kg

Safety certification

FCC Class A, CE Class A, CCC,

Environmental certification

Compliance with RoHS

Accessories

- Windows labeling software CD disk
- USB cable
- Quick start guide
- Power cable
- External universal switching power supply

Applications

- Medical
- Retail POS
- Office
- Shipping
- Shelf labeling

